

# Advanced Thermal Control Technologies for “CEV” (New Name: **ORION**)



Eric Gollither  
NASA Glenn Research Center

David Westheimer and Michael Ewert  
NASA Johnson Space Center

Mojib Hasan  
NASA Glenn Research Center

Molly Anderson and George Tuan  
NASA Johnson Space Center

Duane Beach  
NASA Glenn Research Center


Spacecraft Thermal Control Workshop  
Aerospace Corporation  
March 1, 2007


*The opinion and statements made are my own and do not necessarily reflect NASA's position*



# Abstract

NASA is currently investigating several technology options for advanced human spaceflight. This presentation covers some recent developments that relate to NASA's Orion spacecraft and future Lunar missions.







## **Active Thermal Control Systems (ATCS)**



- Control and maintain a suitable and comfortable environment for the crew and vehicle hardware
  - Has been on every human rated space vehicle
- Historically have utilized single-phase (liquid), pumped fluid loops
- Technologies under development have been targeted for the Crew Exploration Vehicle (CEV), Lunar Surface Access Module (LSAM), and a Lunar Outpost (LO)
- Three main functions
  - Heat Acquisition
  - Heat Transfer
  - Heat Rejection






# Advanced Hardware Research and Development



- Support NASA's Exploration Systems Mission Directorate
- Collaborations
  - Johnson Space Center, Glenn Research Center, Goddard Space Flight Center, and the Jet Propulsion Laboratory
- Industry Partners
  - Hamilton Sundstrand
  - Jacobs-Sverdrup
  - Mainstream
  - Oceaneering Space Systems
  - Paragon Space Development Corporation
  - Sundanzer, Inc.







# Heat Acquisition

Collect waste heat from sources such as Crew life support, avionics, motors, and refrigeration systems

- Liquid cooled coldplates
  - Used on every human rated vehicle that has flown
  - More efficient to transfer heat directly into fluid loop with out heating cabin air
  - More important for CEV due to requirement to depressurize the cabin
  - Provide cooling for electronics
  - Potential Research Areas:
    - Composite coldplates
    - Integrating coldplates into vehicle structure,
    - Thermal interface materials






# Heat Acquisition

Collect waste heat from sources such as Crew life support, avionics, motors, and refrigeration systems

- Air to liquid heat exchangers
  - Control cabin air temperature and humidity
  - Condensate removal and phase separation with either porous material (Apollo) or rotary separator (Shuttle, ISS)
- Liquid to liquid heat exchangers
  - Transfers energy from one fluid loop to another without mixing of fluids
    - Internal to external fluid loops on Shuttle and ISS
  - Scrutinized as a potential failure source
    - A single failure could allow fluids to mix
  - Potential Research Areas:
    - Heat exchangers with two barriers to prevent fluids from mixing



# Heat Transport



Transport heat from heat acquisition hardware to heat rejection hardware

Current state of the art includes:

- Shuttle and ISS use two fluid loops connected by a liquid to liquid heat exchanger
  - **Internal water** loops
  - **External Freon or Ammonia** loop
  - Shuttle and ISS use Water-Freon or Water-Ammonia Interchanger



• Shuttle




• ISS



# Thermal Control System Fluids



- Objective: Find a fluid that can flow inside the crew module as well as outside, eliminate the interchanger
- Technologies Under Development
  - Propylene Glycol “PG” (DOWFROST ▲ “Inhibited”)
    - 60/40 mix of PG/water
    - Very low toxicity, esp. DOWFROST HD
    - Corrosion resistant to Aluminum, esp. DOWFROST
    - However: relatively high viscosity at low temperatures
  - Mainstream is developing other fluids under an SBIR contract with JSC
  - Very Good Summary of non-PG Candidates:  
*Long Life Mechanical Fluid Pump for Space Applications*, Shen, Drolen, Prabhu, Harper, Eichinger, Nguyen




# Thermal Control System Fluids




- Unmanned/Manned Spacecraft have common concerns: Stainless or Aluminum? Or both?

- Materials/Fluids Compatibility

- Aluminum – great heat transfer
- Stainless – great corrosion resistance, lower conductivity
- Dowfrost/Stainless Steel: Good
- Dowfrost/Aluminum: Not as good






# Thermal Control System Fluids




## Recent Activities

- Evaluations have been performed on aqueous Dowfrost HD (inhibited propylene-glycol) solutions with respect to the follow:
  - Low temperature performance
  - Compatibility with life support equipment
  - Flammability (Apollo 1 fire: ethylene glycol)
  - High temperature decomposition by-products
  - Materials compatibility
    - Especially critical for aluminum tubing and heat exchangers
- Potential for microbial activity
- Potential Research Areas
  - Identify or develop new fluids
  - Methods to minimize corrosion in systems with multiple metals (aluminum, SS, nickel) and propylene glycol




Sparks Generated When Ethylene Glycol Drips on Silver Clad Wiring




# Vapor Compression Cycle Heat Pump



- Objective: Demonstrate gravity independent performance of 50°C lift to a heat sink above 300 K
- Technologies Under Development
  - Vapor compression heat pump system
    - 15 kW capacity
    - COP ~3.0
    - Can operate in low to microgravity environments
  - Applicable to Lunar Lander and Lunar Outpost
    - Hot environments during Lunar day





# Vapor Compression Cycle

## Heat Pump



- Recent Activities
  - Evaluating Fairchild 54 mm Helirotor Compressor for performance in different gravity environments
  - Trading compact plate-fin versus tube-in-tube heat exchangers
    - Performed tilt tests on plate fin heat exchangers
    - Performance decreased as a function of tilt angle
- Potential Research Areas
  - Evaporators, condensers, and two-phase mixing devices for use in low to microgravity environments
  - Analysis and testing techniques to evaluate system components and complete systems for performance in different gravity environments
  - Compressors that can operate in different gravity environments or orientations
    - Lubrication and bearing design
  - Effects of gravity on system performance
    - Start up and shutdown
    - System oil management






Plate Fin HX




Tube-in-Tube HX




# Vapor Compression Cycle Heat Pump



- Sinda/Fluint model
  - Compressor
  - Evaporation
  - Condensation






# Heat Rejection




Radiators use heat transfer via radiation to reject energy to space

Current state of the art:

- Aluminum radiators
  - Shuttle and ISS use deployable radiators
  - Gemini and Apollo used body mounted radiators
  - Silver Teflon or Z-93 coating






# Advanced Radiator Developments



- Objectives: Decrease radiator mass and operate during mission transients
- Technologies Under Development
  - Carbon composite radiators
    - Coatings and coating application for composite radiators
    - Integrating flow channels into composite panels
    - MMOD impacts on composite radiators
  - Structurally Integrated Radiator – Paragon Space Development Corp
  - Stagnation flow radiator designs
  - Applicable to all spacecraft




Shuttle Radiator MMOD Damage



JPL/Cal Tech Hypervelocity Test Chamber




Tube Bonding Test Coupon



# Advanced Radiator Developments




- Recent Activities
  - Environmental testing numerous coating coupons
    - Application on carbon composite and aluminum substrates
    - Coatings include Lithium based white paints, OSRs, Electrochromic thin films, Z93, Z93 with different overcoats, Silver Teflon, and S13
    - Environments include thermal cycling, combined UV and Solar Wind, and launch pad weathering
  - Analysis and testing of stagnation radiator concept
  - Testing of tube to panel bond coupons
  - Design and analysis of composite, sandwich panel radiator
  - Thermal and structural testing for Structural Radiators
- Potential Research Areas
  - Applying coatings to composites
  - Integrating flow channels with composites
  - Coating degradation in anticipated environments, including Lunar dust
  - Flow control methods for multiple radiator systems that use propylene glycol based fluids
    - Low temperature viscosity driven stagnation



Stagnation Radiator Manifold



Coating Tests at KSC  
Corrosion Test Facility



# Heat Rejection

Evaporative heat rejection transfers energy into a fluid, causing the fluid to evaporate and the vapor is vented to space

Current state of the art:


- Sublimators
  - Used on Extravehicular Mobility Unit (EMU) and Apollo Lunar Module
  - Self regulating
  - Sensitive to contamination of porous sublimation region
- Fluid Evaporators
  - Previous designs have used water, ammonia, and other fluids
  - Shuttle Flash Evaporator System (FES) sprays water onto a heated surface
  - Shuttle Ammonia boiler is used below 120,000 ft during re-entry and post landing



Apollo LM Sublimator





Shuttle FES



# Contaminant Insensitive Sublimator<sup>TM</sup>


- Objective: Improve sublimator reliability by decreasing sensitivity to contamination in feedwater
- Technology Under Development
  - Developing design of a sublimator with a two stage feedwater distribution
  - Small pore sized material controls the water distribution
  - Freezing and sublimation occur in material with larger pore size
  - Applicable to CEV and Lunar Lander






# Contaminant Insensitive Sublimator

- Recent Activities:
  - Fabricated and tested mini-sublimator
  - Oceanengineering Space Systems fabricated a representative scale sublimator engineering unit
  - Tested at JSC
- Research Areas:
  - Flow and phase change in porous media
    - Multiple pore sizes
    - Flow distribution between porous disks and porous plate
    - Evaporation, freezing, and sublimation




Sublimator Testing



# Multi-environment Evaporative Heat Sink




- Objective: Develop evaporative heat sinks that can operate both in space vacuum and in the Earth's atmosphere post-landing
- Technology Under Development
  - Multi-Fluid Evaporator – uses different fluids for evaporant during different mission phases
  - Flow boiling device
  - Under development by Hamilton Sundstrand
  - Applicable to CEV and Lunar Lander



Multi-Fluid Evaporator Concept







# Multi-environment Evaporative Heat Sink



- Recent Activities
  - Completed flow testing to select fin materials
  - Completed testing of engineering unit to map thermal performance
  - Fabricating a prototype
- Potential Research Areas
  - Evaporating flow through heat transfer fins and porous foams
  - Heat exchanger manufacturing with composites



MFE Engineering Unit




# Compact Flash Evaporator System




- Objective: Provide the maximum heat flux per mass for an evaporative heat sink by spraying evaporant onto a heated surface.

## ● Technology Under Development

- Compact Flash Evaporator System (CFES)
- Sprays onto a flat micro channel heat exchanger
- Utilizes both sides
- Can spray multiple evaporants for both in space and post landing cooling







# Compact Flash Evaporator System




- Recent Activities
  - Single nozzle and nozzle array spray tests in vacuum
  - Single nozzle R 134a spray tests
  - CFES design
- Potential Research Areas
  - Spray optimization over a rectangular surface
  - Control methods for evaporant
  - Correlations for heat transfer of sprays in reduced gravity



Single Nozzle Test



Multi-nozzle Array Testing



# Forward Work



- Complete fabrication of prototype technologies under development that are applicable to CEV
- Thermal vacuum test of integrated Active Thermal Control System made up of prototype technologies
- Evaluate technologies needed for a Lunar lander and Lunar outpost
  - Dust
  - Hot Lunar surface and environments
  - Longer duration technologies
  - Partial gravity
- Evaluate secondary system components
  - valves, instrumentation, fluid connectors and Quick Disconnects